



## SHREDDERS-AND-CHIPPERS

## VERSION | R640DLHP750TRON



## BASIC EQUIPMENT

- ROTOR | Hammers
- Mobile reversible hammers (hardened steel)
- Fixed removable refining screen
- Hydraulic feeding roller with adjustable speed and rotation direction
- Hydraulic feeding conveyor belt in steel with adjustable speed and rotation direction
- Hydraulic discharge conveyor belt in rubber
- Lubrication system for bearings
- Nostress control + SHC system
- Radio remote control for the start-up of the operating controls
- Belt transmission with hydrodynamic joint
- Homologated road trailer + Adjustable drawbar with towing eye
- KOHLER KDI2504TCR
- Electric start

## ACCESSORIES

## CUTTING SYSTEM

Blades (hardened steel)	N°	/
Hammers (hardened steel)	N°	60
Counter-blade	N°	1

## FEATURES

Hourly capacity	m <sup>3</sup> /h*	40 - 60
Throat opening	mm	640 x 200
To shred - Ø max.*	mm	200

## MOTIVE POWER

Power	hp/kW	75 / 55
Power source		Diesel
Engine/motor		KOHLER KDI2504TCR
Fuel consumption	liters/h	12

## SPECIFICATIONS

Length	mm	7415/9050
Width	mm	2015
Height	mm	3270/3090
Discharge height	mm	3090
Introduction height	mm	1650
Hopper size	mm	1500 x ∞ x 3300
Weight: NET	kg	3500

\* Input material - Data depending on the kind of material and working conditions.

**TERMS**

Product origin	Made in Italy
Warranty	The warranty is the one established by law and it's valid just upon submission of the machine's sales document.
Delivery - Original spare parts	Usually available, 45 days max. (from order date)
Identification - SCIP number (link)	<a href="https://echa.europa.eu/it/scip-database">https://echa.europa.eu/it/scip-database</a>

The products are subject to technical evolution and this website may not be fully updated.  
The data in the tables, the photos and pictures have to be considered informative and not binding.