



VACUUMS

VERSION | TORNADOBHP13



BASIC EQUIPMENT

- IMPELLER | 4 paddles
- Paddles in steel
- Suction hose (rigid hose + flexible hose)
- Rotary support for flexible hose
- Folding, rotary ejection pipe with adjustable discharge distance
- Replaceable inner cover
- Twin belt transmission with centrifugal clutch
- Tailboard connection
- HONDA GX390

ACCESSORIES

- Flexible suction hose extension (5000 mm)

VACUUM SYSTEM

Impeller - Ø	mm	390
Paddles (steel)	N°	4
Suction hose - Ø	mm	200

FEATURES

Suction power	m ³ /minute*	150
---------------	-------------------------	-----

MOTIVE POWER

Power	hp/kW	13 / 9,6
Power source		Petrol
Engine/motor		HONDA GX390
Fuel consumption	liters/h	2,8

SPECIFICATIONS

Length	mm	1030/1520
Width	mm	1600
Height	mm	1290/1645
Weight: NET	kg	170
Suction hose length (rigid hose + flexible hose)	mm	1000 + 5000

* Input material - Data depending on the kind of material and working conditions.



TERMS	
Warranty	The warranty is the one established by law and it's valid just upon submission of the machine's sales document.
Product origin	Made in Italy
Delivery - Original spare parts	Usually available, 45 days max. (from order date)
Identification - SCIP number (link)	https://echa.europa.eu/it/scip-database

The products are subject to technical evolution and this website may not be fully updated.
The data in the tables, the photos and pictures have to be considered informative and not binding.